

CAUTION to specifiers requesting **AS1530.1**

See below transcript from The Building Code of Australia.

The Building Code of Australia.

NCC-2001 Building Code of Australia – Volume one

C1.12 Non-combustible materials

The following materials, though combustible or containing combustible fibres, may be used wherever a non-combustible materials required:

- (a) Plasterboard
- (b) Perforated gypsum lath with a normal paper finish
- (c) Fibrous-plaster sheet
- (d) Fibre-reinforced cement sheeting
- (e) Pre-finished metal sheeting having a combustible surface finish not exceeding mm thickness and where the Spread-of-Flame index of the product is not greater than 0.
- (f) Bonded laminated materials where —
 - (i) each laminate is non-combustible; and
 - (ii) Each adhesive layer does not exceed 1mm in thickness; and
**So you can use highly flammable adhesives less than 2mm in total.
We highly recommend you look at alternate solutions where AS1530.1 is called up. In house tests have proven that materials certified AS1530.1 are highly flammable. Nu-core A2FR proves the safest performing ACM/ACP on the market.**
 - (iii) The total thickness of the adhesive layers does not exceed 2mm; and
 - (iv) The Spread-of-Flame Index and the Smoke-Developed Index of the laminated material as a whole does not exceed 0 and 3 respectively